



FEATURES:

- Performance-proven industrial gasoline engine or diesel engines with electric start (battery not included) (air-cooled on MNEQ-5730MORGG-000)
- 2500 watt generator
- Belt drive triplex piston pump with ceramic plungers
- Forged brass manifold with removable valve caps
- Factory preset 3000 PSI—4000 PSI unloader
- Pressure relief valve protects against excessive system pressure
- 80-mesh, high-volume, stainless-steel screen inlet water strainer
- 1/2 inch schedule 80 with steel wrap heat exchanger
- No. 1 or No. 2 fuel oil/diesel/kerosene fired burner
- Raycor fuel/water separator
- Float tank
- 150° F/66° C maximum rise above ambient
- Heavy-duty powder coated steel square tube skid
- Professional-grade insulated trigger gun with safety lock-off
- Adjustable pressure-insulated dual lance with built-in detergent nozzle (0,15,25,40 degrees color-coded quick connect)
- 3/8 inch I.D. x 50 foot steel wire-braided hose with quick connect, swivel and bend restrictors

MODELS	PSI	GPM	HP	ENGINE	Pump	Fuel Cons. per hour	Tank Cap.	BURNER Cons.	Unit Dim. L x W x H (in.)	Ship Wt. Lbs.	Net Wt. Lbs.
MNEQ-4830MOKGG-000	3000	4.8	18.0	Kohler	General	3.37	10.0	3.37	50x34x45	854	750
MNEQ-4830MOVGG-000	3000	4.8	16.0	Vanguard	General	3.37	10.0	3.37	50x34x45	854	764
MNEQ-3835MOKGG-000	3500	3.8	18.0	Kohler	General	3.37	10.0	3.37	50x34x45	854	764
MNEQ-3835MOKVG-000	3500	3.8	16.0	Vanguard	General	3.37	10.0	3.37	50x34x45	854	764
MNEQ-4735MOHGG-000	3500	4.7	20.0	Honda	General	3.37	10.0	3.37	50x34x45	854	764
MNEQ-4735MOKGG-000	3500	4.7	20.0	Kohler	General	3.37	10.0	3.37	50x34x45	854	764
MNEQ-4735MOVGG-000	3500	4.7	21.0	Vanguard	General	3.37	10.0	3.37	50x34x45	854	764
MNEQ-5635MOHGG-000	3500	5.6	24.0	Honda	General	3.37	10.0	3.37	50x34x45	854	764
MNEQ-5635MOKGG-000	3500	5.6	25.0	Kohler	General	3.37	10.0	3.37	50x34x45	854	764
MNEQ-4040MOHGA-000	4000	4.0	20.0	Honda	AR	3.37	10.0	3.37	50x34x45	854	764
MNEQ-4040MOKGA-000	4000	4.0	20.0	Kohler	AR	3.37	10.0	3.37	50x34x45	854	764
MNEQ-4040MOVGA-000	4000	4.0	21.0	Vanguard	AR	3.37	10.0	3.37	50x34x45	854	764
MNEQ-5730MORGG-000	3000	5.7	19.0	Ruggerini	General	3.37	10.0	3.37	50x34x45	854	750
MNEQ-8030MOKGA-000	3000	8.0	25.0	Kohler	AR	3.98	10.0	3.98	50x34x45	868	764

OPTIONS:

MIWV-HX-0130	3 way ball valve	MIEK-HX-0145	Adjustable temperature control
MIWI-HX-0131	High pressure detergent injector (K7)	MIEM-HX-0146	Hour Meter
MIUK-HX-0132-0142	Steam combination 250°	MIUK-HX-0147	Four (4) point lift and lifting hook
MIWV-HX-0143	Trapped Unloader	MIUK-HX-0148	Detergent (trapping unloader)
MIUK-HX-0144	Dual gun (MNEQ-8030MOKGA-000)	MIUK-AW-5740-0000	Wheel Kit
MIUS-50-177	Stack adapter		

